

ESC REST API

ESC REST Northbound API Documentation

Table of Contents

- [Resources managed by ESC REST](#)
- [Behavior of ESC REST operations](#)
- [ESC REST API Headers/Path/Body Parameters](#)
 - [Callbacks](#)
 - [Media Type](#)
 - [Internal IDs](#)
 - [Body](#)
 - [String Restrictions in Body/Internal IDs](#)
- [REST API Security](#)
 - [REST Authentication](#)
 - [REST Https Support](#)
- [REST API List](#)

Resources managed by ESC REST

- Tenants
- Networks
- Subnets
- Flavors
- Images
- Volumes
- Routers
- Deployments

Behavior of ESC REST operations

GET operations are synchronous the request/response parameters are described with an example of a request/response

POST, DELETE, and PUT operations are asynchronous. The asynchronous design use the "web hooks" approach using two independent "one-way" invocations - one to start a long-running operation (Client to ESC) and the other one to notify a requester that it is completed (ESC to client)

ESC REST API Headers/Path/Body Parameters

Callbacks

One of the header parameters of the operation request will contain a callback field, whose value is a URI where the client expects a callback. If this field is not present, no callback will be performed.

When the operation has completed (either successfully or unsuccessfully), ESC will perform a POST request to the callback URI, with an entity body containing the resource for this operation. The status will be returned in the HTTP header called esc-status-code and the status message will be returned in the HTTP header called esc-status-message.

ESC Clients can match a completion report back to the original request by comparing the value of the HTTP header called esc-transaction-id to the one returned in the initial status response.

ESC Clients are expected to provide a REST implementation for all the callbacks.

Media Type

All POST, DELETE, and PUT operations that require request and/or response body must provide a header parameter for media type. Note, that ESC is currently tested to accept and return XML.

Internal IDs

In some of the ESC REST API, there is a path parameter called "*_internal_id" where the asterisk is replaced by the resource type. ESC Clients must provide an internal id for its resource it wants to create. The internal ids are enforced so the ESC Clients are able to refer to them in future operations such as GET, PUT, or DELETE requests.

It is recommended that the ESC Client generated internal ids within the scope of the ESC.

NOTE: Reusing (recycling) of internal ids is not recommended. This practice can lead to confusion in troubleshooting.

Body

In some of the POST, PUT, and DELETE requests you are required to provide a JSON/XML body. Depending on the resource, you will need to provide certain fields in the body to successfully execute a request. Check the body section for each API (bottom of page) to see what fields are supported.

String Restrictions in Body/Internal IDs

Body

Some string parameters/fields, such as id, name, are restricted by the underlying cloud provider, such as Openstack. The allowable range for these parameters is included in the Create section for each resource, in this notation: String minimum-length .. maximum length, for example, for Tenant name: String 1 .. 64

Generally, names are either 1..64 (for Tenant/User) or 1..255 (for Network/Subnet/Flavor/Image/VM).

Internal ID

Ids are restricted to 72 characters such as internal_id 1..72 and external_id 1..72.

Internal id naming must conform the standards stated in RFC 3986 Uniform Resource Identifier (URI): Generic Syntax. See sections related to URI encoding, sections 2.2 Reserved Characters and 2.3 Unreserved Characters. ESC will accept an internal id specified in the request URL from the unreserved character set: unreserved = ALPHA / DIGIT / "-" / ":" / "_"

NOTE: the tilde “~” is not supported in the internal id character set.

The internal id received in a request must be unique within the scope of all the domain resources (tenant, network, subnet, service catalog, deployment) For example, you cannot create 2 networks with the same internal_network_id, even if the networks are created under different tenants.

REST API Security

REST Authentication

Overview

ESC REST API uses http basic access authentication where the ESC client will have to provide a username and password when making ESC REST requests. The user name and password will be encoded with Base64 in transit, but not encrypted or hashed. HTTPS will be used in conjunction with Basic Authentication to provide the encryption.

Setup

By default, the REST authentication is disabled. To enable it pass the argument `--enable-https-rest` and/or `--enable-http-rest` and `--user_rest_pass admin:<password>` to ESC bootvm.py, ESC installation script.

Username and Password

The REST interface has only one default username/password (admin credentials).

The REST password can be updated using escadm tool from the ESC VM CLI:

```
$ escadm rest set --username admin --password <password>
```

You can also update the password through the REST API:

[http://\[ESC_VM_IP\]:8080/ESCManger/v0/authentication/setpassword?
userName=yourUsername&password=yourPassword](http://[ESC_VM_IP]:8080/ESCManger/v0/authentication/setpassword?userName=yourUsername&password=yourPassword)

Sending an Authorized Request

To send an authorized request an ESC client should send the request with the following header:

```
Authorization: Basic <hashed-pass>
```

where is the Base64 enconded string of the default username/password

Most libraries and web clients have an interface for simply providing the username/password and the app will encode the username/password and add the HTTP Basic Auth header.

Example using the default admin credentials:

```
http://[ESC_VM_IP]:8080/ESCManager/v0/tenants/
```

Headers:

```
Content-Type    application/xml  
Authorization   Basic <hashed-pass>
```

RESTHttps Support

Overview

ESC supports https communication over port 8443. ESC will generate a self-signed certificate that the client will need to trust to get the https communication going.

Setup

By default, the REST https is disabled and restricted to localhost. To enable it pass the argument --enable-https-rest to ESC bootvm.py, ESC installation script.

HA Considerations

In an HA setup every ESC HA VM will have its own self-signed generated certificate. Upon an HA switchover, ESC north bound client will be required to re-accept the new certificate it will be served.

REST API List

01-Tenants : Manage ESC tenants

GET

/v0/tenants

Get all tenants

Implementation Notes

All tenants in ESC will be returned as a List

Response Class (Status 200)

Model | Model Schema

```
[  
  {  
    "internal_tenant_id": "string",  
    "external_tenant_id": "string",  
    "name": "string",  
    "enabled": true,  
    "vim_mapping": true,  
    "extensions": {  
      "extension": [  
        {  
          "name": "string",  
          "properties": {  
            "property": [  
              {  
                "name": "string",  
                "value": "string"  
              }  
            ]  
          }  
        }  
      ]  
    }  
  }  
]
```

```

        {
            "name": "string",
            "value": "string"
        }
    ]
},
"containers": {
    "container": [
        {
            "name": "string",
            "properties": {
                "property": [
                    {
                        "name": "string",
                        "value": "string"
                    }
                ]
            }
        }
    ]
},
"event_type": "CREATE_TENANT",
"managed_resource": true
}
]

```

Response Content Type

DELETE /v0/tenants/{internal_tenant_id}

Delete a tenant from ESC

Implementation Notes

Delete a tenant from ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string

Parameter	Value	Description	Parameter Type	Data Type
<code>internal_tenant_id</code>	(required)	Internal tenant ID (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Tenant deletion request accepted		
400	Invalid Request		
404	Invalid Tenant Id		

[Try it out!](#)

GET	/v0/tenants/{internal_tenant_id}	Get a tenant by its name		
Implementation Notes				
Only tenants created using ESC will be checked				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
<code>internal_tenant_id</code>	(required)	Internal tenant ID (max length 72 characters)	path	string
Response Messages				
HTTP Status Code	Reason	Response Model	Headers	
200	Get request accepted			
404	Invalid Request - Invalid Tenant ID			
Try it out!				

POST	/v0/tenants/{internal_tenant_id}	Create a tenant in ESC
Implementation Notes		
Creates a tenant which will be managed by ESC and can be used for creating other resources under it.Example request:		

```
POST /v0/tenants/tentest HTTP/1.1
Content-Type: application/xml
Accept: application/xml
Callback: http://127.0.0.1:9010/
Body:
<tenant xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <name>example-tenant</name>
  <managed_resource>true</managed_resource>
</tenant>
```

After the tenant creation operation is done, ECS will send a callback to the client with the result. Example callback:

```
HTTP/1.1 201 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: d53f0047-2315-466c-b7e3-aa78e0a567e8
ESC-Status-Code: 200
ESC-Status-Message: Tenant successfully created
<tenant xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <enabled>true</enabled>
  <event_type>CREATE_TENANT</event_type>
  <external_tenant_id>484c620285ea4f588227ff3396215980</external_tenant_id>
  <internal_tenant_id>tentest</internal_tenant_id>
  <name>example-tenant</name>
  <managed_resource>true</managed_resource>
</tenant>
```

Parameters

Parameter	Value	Description	Parameter Type	Data Type
-----------	-------	-------------	----------------	-----------

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	Tenant configuration payload	body	<div style="display: flex; justify-content: space-between;"> Model Model Schema </div> <pre>{ "internal_tenant_id": "string", "external_tenant_id": "string", "name": "string", "enabled": true, "vim_mapping": true, "extensions": { "extension": [{ "name": "string", "properties": { "property": [{ "name": "string", "value": "string" }] }], "containers": { "container": [{ "name": "string", "properties": { "property": [{ "name": "string", "value": "string" }] } }] } } }, "event_type": "CREATE_TENANT", "managed_resource": true }</pre> <p>Click to set as parameter value</p>
Callback	(required)	Callback URL for ESC notifications	header	string
internal_tenant_id	(required)	Internal tenant ID (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Tenant creation request accepted		
400	Invalid Request		
409	Conflicting Request		
Try it out!			

PUT

/v0/tenants/{internal_tenant_id}

Update a tenant from ESC

Implementation Notes

Update a tenant from ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	Tenant payload	body	<div style="display: flex; justify-content: space-between;"> Model Model Schema </div> <pre>{ "internal_tenant_id": "string", "external_tenant_id": "string", "name": "string", "enabled": true, "vim_mapping": true, "extensions": { "extension": [{ "name": "string", "properties": { "property": [{ "name": "string", "value": "string" }] }, "containers": { "container": [{ "name": "string", "properties": { "property": [{ "name": "string", "value": "string" }] } }] } }], "event_type": "CREATE_TENANT", "managed_resource": true } }</pre> <p>Click to set as parameter value</p>
Callback	(required)	Callback URL for ESC notifications	header	string

Parameter	Value	Description	Parameter Type	Data Type
<code>internal_tenant_id</code>	(required)	Internal tenant ID (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Tenant update request accepted		
400	Invalid Request		
404	Invalid Tenant Id		
500	Internal Server Error		

[Try it out!](#)

02-Networks : Manage ESC networks

DELETE `/v0/{internalTenantId}/networks/{internalNetworkId}` Delete a network from an existing tenant in ESC

Implementation Notes

Delete a network from ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
<code>Callback</code>	(required)	Callback URL for ESC notifications	header	string
<code>internalNetworkId</code>	(required)	Internal network ID (max length 72 characters)	path	string
<code>internalTenantId</code>	(required)	Internal tenant ID of the network (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		

HTTP Status Code	Reason	Response Model	Headers
400	Invalid request		
500	Internal server error		
Try it out!			

GET /v0/{internalTenantId}/networks/{internalNetworkId} Get a network by its tenant and internal network ID

Implementation Notes

Only networks created using ESC will be checked

Parameters

Parameter	Value	Description	Parameter Type	Data Type
internalTenantId	(required)	Internal tenant ID of the network (max length 72 characters)	path	string
internalNetworkId	(required)	Internal network ID (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
404	Network Id not found		
Try it out!			

POST /v0/{internalTenantId}/networks/{internalNetworkId} Create a network under an existing tenant in ESC

Implementation Notes

Create a network in ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string

Parameter	Value	Description	Parameter Type	Data Type
internalTenantId	(required)	Internal tenant ID of the network (max length 72 characters)	path	string
internalNetworkId	(required)	Internal network ID (max length 72 characters)	path	string

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	Network configuration payload	body	<div style="display: flex; justify-content: space-between;"> Model Model Schema </div> <pre>{ "locator": { "vim_id": "string", "vim_type": "OPENSTACK", "vim_project": "string", "vim_project_id": "string", "vim_region": "string", "vim_vdc": "string" }, "vimNetName": "string", "internal_tenant_id": "string", "internal_network_id": "string", "internal_deployment_id": "string", "name": "string", "shared": true, "external_tenant_id": "string", "tenant_name": "string", "external_network_id": "string", "subnet": ["string"], "admin_state_up": true, "locators": { "datacenter": "string", "switch_name": "string" }, "event_type": "CREATE_NETWORK", "switch_name": "string", "provider_segmentation_id": "string", "router_external": true, "provider_physical_network": "string", "provider_network_type": "string", "vlan_id": 0, "number_of_ports": 0 }</pre> <p>Click to set as parameter value</p>

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid request		
404	Network Id not found		
409	Conflicting request		
503	Unable to query VIM		

Try it out!

GET	/v0/{internalTenantId}/networks	Get all networks under a tenant
-----	---------------------------------	---------------------------------

Implementation Notes

All networks under that tenant in ESC will be returned as a List

Parameters

Parameter	Value	Description	Parameter Type	Data Type
internalTenantId	(required)	Internal tenant ID of the network (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		

Try it out!

03-Subnets : Manage ESC subnets

DELETE	/v0/{internalTenantId}/subnets/{internalSubnetId}	Delete a subnet from an existing tenant in ESC
--------	---	--

Implementation Notes

Delete a subnet from ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalTenantId	(required)	Internal tenant ID of the subnet (max length 72 characters)	path	string
internalSubnetId	(required)	Internal subnet ID (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
404	Not found		
500	Internal server error		

[Try it out!](#)

GET	/v0/{internalTenantId}/subnets/{internalSubnetId}	Get a subnet by its tenant and internal subnet ID
-----	---	---

Implementation Notes

Only subnets created using ESC will be checked

Parameters

Parameter	Value	Description	Parameter Type	Data Type
internalTenantId	(required)	Internal tenant ID of the subnet (max length 72 characters)	path	string
internalSubnetId	(required)	Internal subnet ID (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
404	Not found		

[Try it out!](#)

POST	/v0/{internalTenantId}/subnets/{internalSubnetId}	Create a subnet under an existing tenant in ESC
------	---	---

Implementation Notes

Create a subnet in ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
-----------	-------	-------------	----------------	-----------

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalTenantId	(required)	Internal tenant ID of the subnet (max length 72 characters)	path	string
internalSubnetId	(required)	Internal subnet ID (max length 72 characters)	path	string
body	(required)	Subnet configuration payload	body	<div> Model Model Schema </div> <pre>{ "networkFromCdg": { "locator": { "vim_id": "string", "vim_type": "OPENSTACK", "vim_project": "string", "vim_project_id": "string", "vim_region": "string", "vim_vdc": "string" }, "vimNetName": "string", "internal_tenant_id": "string", "internal_network_id": "string", "internal_deployment_id": "string", "name": "string", "shared": true, "external_tenant_id": "string", "tenant_name": "string", "external_network_id": "string", "subnet": ["string"], "admin_state_up": true, "locators": { "datacenter": "string", "switch_name": "string" }, "event_type": "CREATE_NETWORK", "switch_name": "string", "provider_segmentation_id": "string", "router_external": true, "provider_physical_network": "string", "segmentation_id": "string" } }</pre>
Parameter content type:		application/xml ▾		

Parameter	Value	Description	Parameter Type	Data Type
				<pre> "provider_network_type": "string", "vlan_id": 0, "number_of_ports": 0 }, "internal_tenant_id": "string", "external_tenant_id": "string", "internal_network_id": "string", "external_network_id": "string", "internal_subnet_id": "string", "external_subnet_id": "string", "name": "string", "allocation_pools": [{ "start": "string", "end": "string" }], "gateway_ip": "string", "ip_version": 0, "cidr": "string", "enable_dhcp": true, "event_type": "CREATE_SUBNET" } </pre>

Click to set as parameter value

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
404	Not found		
409	Conflicting Request		
500	Internal server error		

[Try it out!](#)

GET	/v0/{internalTenantId}/subnets	Get all subnets under a network
-----	--------------------------------	---------------------------------

Implementation Notes

All subnet under that network in ESC will be returned as a List

Parameters

Parameter	Value	Description	Parameter Type	Data Type

Parameter	Value	Description	Parameter Type	Data Type
internalNetworkId	<input type="text"/>	Internal network ID of the subnet (max length 72 characters)	header	string
internalTenantId	<input type="text" value="(required)"/>	Internal tenant ID of the subnet (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
404	Not found		

[Try it out!](#)

04-Images : Manage ESC images

DELETE	/v0/images/{internalImageId}	Delete an image from ESC		
Implementation Notes				
Delete an image from ESC				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
Callback	<input type="text" value="required"/>	Callback URL for ESC notifications	header	string
internalImageId	<input type="text" value="required"/>	Internal image ID (max length 72 characters)	path	string
Response Messages				
HTTP Status Code	Reason	Response Model	Headers	
200	Request accepted			
400	Invalid Request			
500	Internal server error			

[Try it out!](#)

GET

/v0/images/{internalImageId}

Get the image by the internal image ID

Implementation Notes

Images not created by ESC will not be checked

Parameters

Parameter	Value	Description	Parameter Type	Data Type
internalImageId	(required)	Internal image ID (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
404	Image Id not found		

[Try it out!](#)

POST /v0/images/{internalImageId} Create an image in ESC

Implementation Notes

Creates an Image(Template) which will be managed by ESC and can be used for creating instance VMs. An optional properties list can be included in the image creation payload. This is only supported for creation of images on openstack. Image properties will be stored in openstack as image metadata. Property name and values are not validated by ESC.

Example 1 create image request (without properties):

```
POST /v0/images/my_image_id HTTP/1.1
Content-Type: application/xml
Accept: application/xml
Callback: http://127.0.0.1:9010/
Body:

<?xml version="1.0"?>
<image xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
    <name>uLinuxImg</name>
    <src>http://VAR_FILE_SERVER_IP/share/images/myULinux.qcow2</src>
    <disk_bus>virtio</disk_bus>
</image>
```

Example 2 create image request with properties:

```
POST /v0/images/my_image_id HTTP/1.1
Content-Type: application/xml
Accept: application/xml
Callback: http://127.0.0.1:9010/
Body:

<?xml version="1.0"?>
<image xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
    <name>uLinuxImg</name>
    <src>http://VAR_FILE_SERVER_IP/share/images/myULinux.qcow2</src>
    <disk_bus>virtio</disk_bus>
    <properties>
        <property>
            <name>os_secure_boot</name>
            <value>enabled</value>
        </property>
        <property>
            <name>hw_rng_model</name>
            <value>virtio</value>
        </property>
        <property>
            <name>hw_vif_multiqueue_enabled</name>
            <value>true</value>
        </property>
    </properties>
</image>
```

Example 3 create image with properties Use of image properties allow flexible assignment of image metadata, such as hw_disk_bus and hw_vif_model. This extends current limitation of ESC schema with disk_bus := ide | scsi | virtio and e1000_net := true | false and virtio_net := true | false.

```
POST /v0/images/my_image_id HTTP/1.1
Content-Type: application/xml
Accept: application/xml
Callback: http://127.0.0.1:9010/
Body:

<?xml version="1.0"?>
<image xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
    <name>uLinuxImg</name>
    <src>http://VAR_FILE_SERVER_IP/share/images/myULinux.qcow2</src>
    <disk_bus>virtio</disk_bus>
    <properties>
        <property>
            <name>hw_disk_bus</name>
            <value>pcnet</value>
        </property>
    </properties>
</image>
```

```

<property>
  <name>hw_vif_model</name>
  <value>pcnet</value>
</property>
</properties>
</image>

```

After the Image creation operation is done, ESC will send a callback to the client with the result.

Example callback:

```

HTTP/1.1 201 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: d53f0047-2315-466c-b7e3-aa78e0a567e8
ESC-Status-Code: 200
ESC-Status-Message: Image successfully created

```

```

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<image xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <disk_bus>virtio</disk_bus>
  <e1000_net>false</e1000_net>
  <event_type>CREATE_IMAGE</event_type>
  <external_image_id>5021843b-fcc5-2c1b-8fc4-935147f95872</external_image_id>
  <external_tenant_id>SystemAdminTenantId</external_tenant_id>
  <imageisenabled>true</imageisenabled>
  <name>uLinuxImg</name>
  <internal_image_id>my_image_id</internal_image_id>
  <internal_tenant_id>SystemAdminTenantId</internal_tenant_id>
  <visibility>public</visibility>
  <src>http://VAR_FILE_SERVER_IP/share/images/myULinux.qcow2</src>
</image>

```

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalImageId	(required)	Internal image ID (max length 72 characters)	path	string

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	ESC datamodel with the image to create	body	string

Parameter content type:
application/xml ▾

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
409	Conflicting Request		
500	Internal server error		

[Try it out!](#)

GET	/v0/images	Get all images
Implementation Notes		
All images created in ESC will be returned as a List		
Response Messages		

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		

[Try it out!](#)

DELETE	/v0/flavors/{internalFlavorId}	Delete a flavor from ESC
Implementation Notes		
Delete a flavor from ESC		
Parameters		

Parameter	Value	Description	Parameter Type	Data Type
-----------	-------	-------------	----------------	-----------

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalFlavorId	(required)	Internal flavor ID (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
404	Flavor Id not found		
500	Internal server error		

[Try it out!](#)

GET	/v0/flavors/{internalFlavorId}	Get the flavor by the internal flavor ID		
Implementation Notes				
Flavors not created by ESC will not be checked				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
internalFlavorId	(required)	Internal flavor ID (max length 72 characters)	path	string
Response Messages				
HTTP Status Code	Reason	Response Model	Headers	
200	Request accepted			
404	Flavor Id not found			
406	Operation not supported on VIM/Flavor part of service registration			
Try it out!				

POST	/v0/flavors/{internalFlavorId}	Create a flavor in ESC
------	--------------------------------	------------------------

Implementation Notes

Creates a Flavor which could be used for creating instance VMs.

Example request:

```
POST /v0/flavors/my_flavor_id HTTP/1.1
Content-Type: application/xml
Accept: application/xml
Callback: http://127.0.0.1:9010/
Body:
<?xml version="1.0"?>
<flavor xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
    <name>lightVMFlavor</name>
    <vcpus>2</vcpus>
    <memory_mb>2048</memory_mb>
</flavor>
```

After the Flavor creation operation is done, ESC will send a callback to the client with the result.

Example callback:

```
HTTP/1.1 201 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: d53f0047-2315-466c-b7e3-aa78e0a567e8
ESC-Status-Code: 200
ESC-Status-Message: Flavor creation completed successfully created
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<flavor xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
    <ephemeral_disk_mb>0</ephemeral_disk_mb>
    <event_type>CREATE_FLAVOR</event_type>
    <external_flavor_id>fb63c114-de1a-40d8-abae-fa6011abd150</external_flavor_id>
    <name>lightVMFlavor</name>
    <internal_flavor_id>my_flavor_id</internal_flavor_id>
    <memory_mb>2048</memory_mb>
    <vcpus>2</vcpus>
</flavor>
```

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalFlavorId	(required)	Internal flavor ID (max length 72 characters)	path	string

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	ESC datamodel with the flavor to create	body	string
Parameter content type:				
application/xml ▾				

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
404	Flavor Id not found		
406	Operation not supported on VIM/Flavor part of service registration		
409	Conflicting Request		
500	Internal server error		

Try it out!

GET	/v0/flavors	Get all flavors								
Implementation Notes										
All flavors created in ESC will be returned as a List										
Response Messages										
<table border="1"> <thead> <tr> <th>HTTP Status Code</th><th>Reason</th><th>Response Model</th><th>Headers</th></tr> </thead> <tbody> <tr> <td>200</td><td>Request accepted</td><td></td><td></td></tr> </tbody> </table>			HTTP Status Code	Reason	Response Model	Headers	200	Request accepted		
HTTP Status Code	Reason	Response Model	Headers							
200	Request accepted									
Try it out!										

06-Deployments : Manage ESC deployments

DELETE	/v0/deployments/{internal_deployment_id}	Delete a deployment from ESC
Implementation Notes		

Delete a deployment from ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	<input type="text" value="(required)"/>	Callback URL for ESC notifications	header	string
internal_deployment_id	<input type="text" value="(required)"/>	Internal ID of the deployment (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
404	Deployment Id not found		

[Try it out!](#)

GET

/v0/deployments/{internal_deployment_id}

Find a deployment by its internal ID

Implementation Notes

A deployment will be returned if found in ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Accept	<input type="text"/>		header	string
internal_deployment_id	<input type="text" value="(required)"/>	Internal ID of the deployment (max length 1024 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
404	Deployment Id not found		

[Try it out!](#)

POST

/v0/deployments/{internal_deployment_id}

Creates a deployment

Implementation Notes

Creates a Simple deployment of Instance VMs.

NOTE: As deployment requirements vary a lot, please see ESC User guide for datamodel excerpts of specific functionality you may desire that's not displayed in the simple example below.

Example request:

```
POST /v0/deployments/my_dep_id HTTP/1.1
Content-Type: application/xml
Accept: application/xml
Callback: http://127.0.0.1:9010/
Callback-ESC-Events: http://127.0.0.1:9010/
```

Body:

```
<esc_datamodel xmlns="http://www.cisco.com/esc/esc" xmlns:ns2="urn:ietf:params:xml:ns:netconf:notification:1.0">
  <tenants>
    <tenant>
      <name>admin</name>
      <deployments>
        <deployment>
          <name>MyDemoDepName</name>
          <vm_group>
            <name>ASA-1</name>
            <bootup_time>300</bootup_time>
            <reboot_time>100</reboot_time>
            <recovery_wait_time>10</recovery_wait_time>
            <image>ASA</image>
            <interfaces>
              <interface>
                <nicid>1</nicid>
                <network>MgtNetwork</network>
                <ip_address>18.0.0.16</ip_address>
              </interface>
            </interfaces>
            <scaling>
              <min_active>1</min_active>
              <max_active>1</max_active>
              <elastic>true</elastic>
              <static_ip_address_pool>
                <network>MgtNetwork</network>
                <ip_address>18.0.0.16</ip_address>
              </static_ip_address_pool>
            </scaling>
            <kpi_data>
              <kpi>
```

```

<event_name>VM_ALIVE</event_name>
<metric_value>1</metric_value>
<metric_cond>GT</metric_cond>
<metric_type>UINT32</metric_type>
<metric_collector>
    <type>ICMPPing</type>
    <nicaid>1</nicaid>
    <poll_frequency>3</poll_frequency>
    <polling_unit>seconds</polling_unit>
    <continuous_alarm>false</continuous_alarm>
</metric_collector></kpi>
</kpi_data>
<rules>
    <admin_rules>
        <rule>
            <event_name>VM_ALIVE</event_name>
            <action>"ALWAYS log"</action>
            <action>"TRUE esc_vm_alive_notification"</action>
        </rule>
    </admin_rules>
</rules>
<config_data>
    <configuration>
        <dst>day0-config</dst>
        <file>http://MY_FILE_SERVER_IP:/share/images/day0-configASAv</file>
    </configuration>
    <configuration>
        <dst>idtoken</dst>
        <file>http://MY_FILE_SERVER_IP:/share/images/asa-smart.config</file>
    </configuration>
</config_data>
<placement>
    <type>zone_host</type>
    <zone>MY_CLUSTER1</zone>
</placement>
<volumes>
    <volume>
        <name>MY_DATASTORE1</name>
        <volid>1</volid>
    </volume>
</volumes>
</vm_group>
</deployment>
</deployments>
</tenant>
</tenants>
</esc_datamodel>

```

While the Deployment operation is being processed successfully, ESC will send a VM_DEPLOYED callback for each VM created on the VIM as part of this deployment

```

HTTP/1.1 201 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: d53f0047-2315-466c-b7e3-aa78e0a567e8
ESC-Status-Code: 200
ESC-Status-Message: VM Deployed

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<deployment xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
    <datacenter>
        <default>false</default>
    </datacenter>
    <deployment_details>
        <host_uuid>host-14882</host_uuid>
        <host_name>10.85.103.13</host_name>
        <vm_uuid>50217d2d-8afb-41c2-cffd-d76b1239f51d</vm_uuid>
        <interfaces>
            <interface>
                <network_uuid>MgtNetwork</network_uuid>
                <ip_address>18.0.0.16</ip_address>
                <mac_address>00:50:56:a1:6a:12</mac_address>
                <nic_id>1</nic_id>
                <port_forwarding></port_forwarding>
                <port_uuid></port_uuid>
                <security_groups></security_groups>
                <subnet_uuid></subnet_uuid>
                <type>virtual</type>
            </interface>
        </interfaces>
        <vm_group_name>ASA-1</vm_group_name>
        <vm_name>Sanity-vmware-de_ASA-1_0_b323effd-7f70-4055-b11e-0ef66f0a758d</vm_name>
        <vm_state_machine_state>VM_INSERT_STATE</vm_state_machine_state>
    </deployment_details>
    <deployment_name>MyDemoDepName</deployment_name>
    <deployment_stage>VM_DEPLOYED</deployment_stage>
    <external_deployment_id>8d084aab-6a66-4a70-8f47-42b91f7477ac</external_deployment_id>
    <external_tenant_id>SystemAdminTenantId</external_tenant_id>
    <internal_deployment_id>my_dep_id</internal_deployment_id>
    <internal_tenant_id>SystemAdminTenantId</internal_tenant_id>
    <service_state_machine_state>SERVICE_DEPLOYING_STATE</service_state_machine_state>
</deployment>

```

While the Deployment operation is being processed successfully, ESC will send a VM_ALIVE callback for each monitorable/pingable VM created on the VIM as part of this deployment

```

HTTP/1.1 201 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: d53f0047-2315-466c-b7e3-aa78e0a567e8
ESC-Status-Code: 200
ESC-Status-Message: VM_Alive event received, VM ID: [Sanity-vmware-de_ASA-1_0_b323effd-7f70-4055-b11e-0ef66f

```

```

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<deployment xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <datacenter>
    <default>false</default>
  </datacenter>
  <deployment_details>
    <host_uuid>host-14882</host_uuid>
    <host_name>10.85.103.13</host_name>
    <vm_uuid>50217d2d-8afb-41c2-cffd-d76b1239f51d</vm_uuid>
    <interfaces>
      <interface>
        <network_uuid>MgtNetwork</network_uuid>
        <ip_address>18.0.0.16</ip_address>
        <mac_address>00:50:56:a1:6a:12</mac_address>
        <nic_id>1</nic_id>
        <port_forwarding></port_forwarding>
        <port_uuid></port_uuid>
        <security_groups></security_groups>
        <subnet_uuid></subnet_uuid>
        <type>virtual</type>
      </interface>
    </interfaces>
    <vm_group_name>ASA-1</vm_group_name>
    <vm_name>Sanity-vmware-de_ASA-1_0_b323effd-7f70-4055-b11e-0ef66f0a758d</vm_name>
    <vm_state_machine_state>VM_ALIVE_STATE</vm_state_machine_state>
  </deployment_details>
  <deployment_name>MyDemoDepName</deployment_name>
  <deployment_stage>VM_ALIVE</deployment_stage>
  <external_deployment_id>8d084aab-6a66-4a70-8f47-42b91f7477ac</external_deployment_id>
  <external_tenant_id>SystemAdminTenantId</external_tenant_id>
  <internal_deployment_id>my_dep_id</internal_deployment_id>
  <internal_tenant_id>SystemAdminTenantId</internal_tenant_id>
  <service_state_machine_state>SERVICE_INSERT_STATE</service_state_machine_state>
</deployment>

```

After the Deployment operation is done, ESC will send a SERVICE_ALIVE callback to the client with the result.

Example callback:

```

HTTP/1.1 201 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: d53f0047-2315-466c-b7e3-aa78e0a567e8
ESC-Status-Code: 200
ESC-Status-Message: Service group deployment completed successfully!

```

```

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<deployment xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <datacenter>
    <default>false</default>
  </datacenter>

```

```

</datacenter>
<deployment_name>MyDemoDepName</deployment_name>
<deployment_stage>SERVICE_ALIVE</deployment_stage>
<external_deployment_id>8d084aab-6a66-4a70-8f47-42b91f7477ac</external_deployment_id>
<external_tenant_id>SystemAdminTenantId</external_tenant_id>
<internal_deployment_id>my_dep_id</internal_deployment_id>
<internal_tenant_id>SystemAdminTenantId</internal_tenant_id>
<service_state_machine_state>SERVICE_ACTIVE_STATE</service_state_machine_state>
</deployment>

```

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
Callback-ESC-Events	(required)	Callback URL for ESC event notifications	header	string
internal_deployment_id	(required)	Internal ID of the deployment (max length 72 characters)	path	string
body	(required)	ESC datamodel to deploy	body	string

Parameter content type:

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
404	An associated resource not found		
406	Not Acceptable		
409	Conflicting Request		
500	Internal server error		
503	Failed to query VIM		

Try it out!

PUT	/v0/deployments/{internal_deployment_id}	Update an existing deployment in ESC
-----	--	--------------------------------------

Implementation Notes

Updates an existing deployment. Updates could be addition or removal of VM groups, interfaces, networks, KPIs and Rules, Day 0 config.

After the service update operation is done, ESC will send a callback to the client with the result.

Example request of adding VM group:

```
PUT /v0/deployments/my_dep_id HTTP/1.1
Content-Type: application/xml
Accept: application/xml
Callback: http://127.0.0.1:9010/
Callback-ESC-Events: http://127.0.0.1:9010/
```

Body:

```
<esc_datamodel xmlns:ns2="urn:ietf:params:xml:ns:netconf:notification:1.0" xmlns="http://www.cisco.com/e
<tenants>
<tenant>
<name>admin</name>
<deployments>
<deployment>
<name>MyDemoDepName</name>
<vm_group>
<name>ASA-1</name>
<bootup_time>300</bootup_time>
<recovery_wait_time>0</recovery_wait_time>
<image>ASA</image>
<interfaces>
<interface>
<nicid>1</nicid>
<network>MgtNetwork</network>
<ip_address>18.0.0.16</ip_address>
</interface>
</interfaces>
<scaling>
<min_active>1</min_active>
<max_active>1</max_active>
<elastic>true</elastic>
<static_ip_address_pool>
<network>MgtNetwork</network>
<ip_address>18.0.0.16</ip_address>
</static_ip_address_pool>
</scaling>
```

```
<kpi_data>
<kpi>
  <event_name>VM_ALIVE</event_name>
  <metric_value>1</metric_value>
  <metric_cond>GT</metric_cond>
  <metric_type>UINT32</metric_type>
  <metric_collector>
    <type>ICMPPing</type>
    <nicaid>1</nicaid>
    <poll_frequency>3</poll_frequency>
    <polling_unit>seconds</polling_unit>
    <continuous_alarm>false</continuous_alarm>
  </metric_collector></kpi>
</kpi_data>
<rules>
  <admin_rules>
    <rule>
      <event_name>VM_ALIVE</event_name>
      <action>"ALWAYS log"</action>
      <action>"TRUE esc_vm_alive_notification"</action>
    </rule>
  </admin_rules>
</rules>
<config_data>
  <configuration>
    <dst>day0-config</dst>
    <file>http://MY_FILE_SERVER_IP:/share/images/day0-configASA</file>
  </configuration>
  <configuration>
    <dst>idtoken</dst>
    <file>http://MY_FILE_SERVER_IP:/share/images/asa-smart.config</file>
  </configuration>
</config_data>
<placement>
  <type>zone_host</type>
  <zone>MY_CLUSTER1</zone>
</placement>
<volumes>
  <volume>
    <name>MY_DATASTORE1</name>
    <volid>1</volid>
  </volume>
</volumes>
</vm_group>
<name>CSR-1</name>
<bootup_time>300</bootup_time>
<recovery_wait_time>0</recovery_wait_time>
<image>ASA</image>
<interfaces>
  <interface>
    <nicaid>1</nicaid>
```

```
<network>MgtNetwork</network>
<ip_address>18.0.0.16</ip_address>
</interface>
</interfaces>
<scaling>
<min_active>1</min_active>
<max_active>1</max_active>
<elastic>true</elastic>
<static_ip_address_pool>
<network>MgtNetwork</network>
<ip_address>18.0.0.16</ip_address>
</static_ip_address_pool>
</scaling>
<kpi_data>
<kpi>
<event_name>VM_ALIVE</event_name>
<metric_value>1</metric_value>
<metric_cond>GT</metric_cond>
<metric_type>UINT32</metric_type>
<metric_collector>
<type>ICMPPing</type>
<nicaid>1</nicaid>
<poll_frequency>3</poll_frequency>
<polling_unit>seconds</polling_unit>
<continuous_alarm>false</continuous_alarm>
</metric_collector></kpi>
</kpi_data>
<rules>
<admin_rules>
<rule>
<event_name>VM_ALIVE</event_name>
<action>"ALWAYS log"</action>
<action>"TRUE esc_vm_alive_notification"</action>
</rule>
</admin_rules>
</rules>
<config_data>
<configuration>
<dst>day0-config</dst>
<file>http://MY_FILE_SERVER_IP:/share/images/day0-configASA</file>
</configuration>
<configuration>
<dst>idtoken</dst>
<file>http://MY_FILE_SERVER_IP:/share/images/asa-smart.config</file>
</configuration>
</config_data>
<placement>
<type>zone_host</type>
<zone>MY_CLUSTER1</zone>
</placement>
<volumes>
```

```

<volume>
  <name>MY_DATASTORE1</name>
  <volid>1</volid>
</volume>
</volumes>

</deployment>
</deployments>
</tenant>
</tenants>
</esc_datamodel>

```

While the Deployment Update operation is being processed successfully, ESC will send a VM_DEPLOYED callback for each VM created on the VIM as part of this update request.

```

HTTP/1.1 201 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: d53f0047-2315-466c-b7e3-aa78e0a567e8
ESC-Status-Code: 200
ESC-Status-Message: VM Deployed

```

```

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<deployment xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
<datacenter><default>false</default></datacenter>
<deployment_details>
<host_uuid>host-14882</host_uuid>
<host_name>10.85.103.13</host_name>
<vm_uuid>50217d2d-8afb-41c2-cffd-d76b1239f51e</vm_uuid>
<interfaces>
<interface>
<network_uuid>MgtNetwork</network_uuid>
<ip_address>18.0.0.17</ip_address>
<mac_address>00:50:56:a1:6a:13</mac_address>
<nic_id>1</nic_id>
<port_forwarding></port_forwarding>
<port_uuid></port_uuid>
<security_groups></security_groups>
<subnet_uuid></subnet_uuid>
<type>virtual</type>
</interface>
</interfaces>
<vm_group_name>CSR-1</vm_group_name>
<vm_name>Sanity-vmware-de_CSR-1_0_b323effd-7f70-4055-b11e-0ef66f0a758d</vm_name>
<vm_state_machine_state>VM_INSERT_STATE</vm_state_machine_state>
</deployment_details>
<deployment_name>MyDemoDepName</deployment_name>
<deployment_stage>VM_DEPLOYED</deployment_stage>
<external_deployment_id>8d084aab-6a66-4a70-8f47-42b91f7477ad</external_deployment_id>
<external_tenant_id>SystemAdminTenantId</external_tenant_id>
<internal_deployment_id>my_dep_id</internal_deployment_id>

```

```
<internal_tenant_id>SystemAdminTenantId</internal_tenant_id>
<service_state_machine_state>SERVICE_DEPLOYING_STATE</service_state_machine_state>
</deployment>
```

While the Deployment Update operation is being processed successfully, ESC will send a VM_ALIVE callback for each monitorable/pingable VM on the VIM created as part of this update request.

```
HTTP/1.1 201 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: d53f0047-2315-466c-b7e3-aa78e0a567e8
ESC-Status-Code: 200
ESC-Status-Message: VM_Alive event received, VM ID: [Sanity-vmware-de_CSR-1_0_b323effd-7f70-4055-b11e-0ef66f

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<deployment xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
<datacenter><default>false</default></datacenter>
<deployment_details>
<host_uuid>host-14882</host_uuid>
<host_name>10.85.103.13</host_name>
<vm_uuid>50217d2d-8afb-41c2-cffd-d76b1239f51e</vm_uuid>
<interfaces>
<interface>
<network_uuid>MgtNetwork</network_uuid>
<ip_address>18.0.0.17</ip_address>
<mac_address>00:50:56:a1:6a:13</mac_address>
<nic_id>1</nic_id>
<port_forwarding></port_forwarding>
<port_uuid></port_uuid>
<security_groups></security_groups>
<subnet_uuid></subnet_uuid>
<type>virtual</type>
</interface>
</interfaces>
<vm_group_name>CSR-1</vm_group_name>
<vm_name>Sanity-vmware-de_CSR-1_0_b323effd-7f70-4055-b11e-0ef66f0a758d</vm_name>
<vm_state_machine_state>VM_ALIVE_STATE</vm_state_machine_state>
</deployment_details>
<deployment_name>MyDemoDepName</deployment_name>
<deployment_stage>VM_ALIVE</deployment_stage>
<external_deployment_id>8d084aab-6a66-4a70-8f47-42b91f7477ac</external_deployment_id>
<external_tenant_id>SystemAdminTenantId</external_tenant_id>
<internal_deployment_id>my_dep_id</internal_deployment_id>
<internal_tenant_id>SystemAdminTenantId</internal_tenant_id>
<service_state_machine_state>SERVICE_INSERT_STATE</service_state_machine_state>
</deployment>
```

After the Deployment Update operation is done, ESC will send a SERVICE_UPDATED callback to the client with the result.

Example callback:

```
HTTP/1.1 201 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: d53f0047-2315-466c-b7e3-aa78e0a567e8
ESC-Status-Code: 200
ESC-Status-Message: Service group update completed successfully
```

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<deployment xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
<datacenter><default>false</default></datacenter>
<deployment_name>MyDemoDepName</deployment_name>
<deployment_stage>SERVICE_UPDATED</deployment_stage>
<external_deployment_id>8d084aab-6a66-4a70-8f47-42b91f7477ac</external_deployment_id>
<external_tenant_id>SystemAdminTenantId</external_tenant_id>
<internal_deployment_id>my_dep_id</internal_deployment_id>
<internal_tenant_id>SystemAdminTenantId</internal_tenant_id>
<service_state_machine_state>SERVICE_ACTIVE_STATE</service_state_machine_state>
</deployment>
```

If a VM specific resource like interface, is updated, then a VM_UPDATED followed by a SERVICE_UPDATED notification is received.

Example callback:

```
HTTP/1.1 201 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: d53f0047-2315-466c-b7e3-aa78e0a567e8
ESC-Status-Code: 200
ESC-Status-Message: VM has been updated successfully. vm: VM ID: [Sanity-vmware-de_CSR-1_0_b323effd-7f70-405
```

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<deployment xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
<datacenter><default>false</default></datacenter>
<deployment_details>
<host_uuid>host-14882</host_uuid>
<host_name>10.85.103.13</host_name>
<vm_uuid>50217d2d-8afb-41c2-cffd-d76b1239f51e</vm_uuid>
<interfaces>
<interface>
<network_uuid>MgtNetwork</network_uuid>
<ip_address>18.0.0.17</ip_address>
<mac_address>00:50:56:a1:6a:13</mac_address>
<nic_id>1</nic_id>
<port_forwarding></port_forwarding>
<port_uuid></port_uuid>
<security_groups></security_groups>
<subnet_uuid></subnet_uuid>
<type>virtual</type>
</interface>
<interface>
```

```

<network_uuid>MgtNetwork2</network_uuid>
<ip_address>18.0.1.18</ip_address>
<mac_address>00:50:56:a1:6b:14</mac_address>
<níc_id>2</níc_id>
<port_forwarding></port_forwarding>
<port_uuid></port_uuid>
<security_groups></security_groups>
<subnet_uuid></subnet_uuid>
<type>virtual</type>
</interface>
</interfaces>
<vm_group_name>CSR-1</vm_group_name>
<vm_name>Sanity-vmware-de_CSR-1_0_b323effd-7f70-4055-b11e-0ef66f0a758d</vm_name>
<vm_state_machine_state>VM_ALIVE_STATE</vm_state_machine_state>
</deployment_details>
<deployment_name>MyDemoDepName</deployment_name>
<deployment_stage>VM_ALIVE</deployment_stage>
<external_deployment_id>8d084aab-6a66-4a70-8f47-42b91f7477ac</external_deployment_id>
<external_tenant_id>SystemAdminTenantId</external_tenant_id>
<internal_deployment_id>my_dep_id</internal_deployment_id>
<internal_tenant_id>SystemAdminTenantId</internal_tenant_id>
<service_state_machine_state>SERVICE_INERT_STATE</service_state_machine_state>
</deployment>
```

Followed by:

```

HTTP/1.1 201 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: d53f0047-2315-466c-b7e3-aa78e0a567e8
ESC-Status-Code: 200
ESC-Status-Message: Service group update completed successfully
```

```

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<deployment xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
<datacenter><default>false</default></datacenter>
<deployment_name>MyDemoDepName</deployment_name>
<deployment_stage>SERVICE_UPDATED</deployment_stage>
<external_deployment_id>8d084aab-6a66-4a70-8f47-42b91f7477ac</external_deployment_id>
<external_tenant_id>SystemAdminTenantId</external_tenant_id>
<internal_deployment_id>my_dep_id</internal_deployment_id>
<internal_tenant_id>SystemAdminTenantId</internal_tenant_id>
<service_state_machine_state>SERVICE_ACTIVE_STATE</service_state_machine_state>
</deployment>
```

Parameters

Parameter	Value	Description	Parameter Type	Data Type
-----------	-------	-------------	----------------	-----------

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
Callback-ESC-Events	(required)	Callback URL for ESC event notifications	header	string
internal_deployment_id	(required)	Internal ID of the deployment (max length 72 characters)	path	string
body	(required)	ESC datamodel to update	body	string

Parameter content type:

application/xml ▾

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
404	An associated resource not found		
406	Not Acceptable		
409	Conflicting Request		
500	Internal server error		

Try it out!

GET	/v0/deployments	Find all deployments
-----	-----------------	----------------------

Implementation Notes

All deployments created in ESC will be returned as a List

Parameters

Parameter	Value	Description	Parameter Type	Data Type
-----------	-------	-------------	----------------	-----------

Parameter	Value	Description	Parameter Type	Data Type
Accept	<input type="text"/>		header	string
Response Messages				
HTTP Status Code	Reason	Response Model	Headers	
200	Request accepted			
Try it out!				

GET	/v0/deployments/config/{internal_deployment_id}	Find deployment configuration data by its internal ID		
Implementation Notes				
Deployment configuration data will be returned if found in CDB				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
internal_deployment_id	<input type="text" value="required"/>	Internal ID of the deployment (max length 1024 characters)	path	string

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
404	Deployment Id not found		
Try it out!			

07-Deployment Operations : Operations to a deployment

POST	/v0/{internal_tenant_id}/deployments/service/{internal_deployment_id}	Handle deployment operation request with the operation type as payload
Implementation Notes		
Performs actions like stop, start, reboot, disable_monitoring or enable_monitoring on a deployment. Example request:		
<pre>POST /v0/tenants/test-tenant1/deployments/vm/test-dep1-cirros_overid_0_cfeefcee-a1fe-4e94-9ffc-81792b265788 Content-Type: application/xml</pre>		

```
Accept: application/json
Callback: http://127.0.0.1:9010/
```

Body:

```
<service_operation xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <operation>stop</operation>
</service_operation>
```

While the stop deployment operation is being performed, ESC will send a VM_STOPPED callback to the client for each VM stopped as part of this request. Example callback:

```
HTTP/1.1 200 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: 5e47b5ff-bc59-4ece-b15b-8941910def74
ESC-Status-Code: 200
ESC-Status-Message: VM successfully stopped

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<deployment xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <datacenter>
    <default>false</default>
  </datacenter>
  <deployment_details>
    <host_uuid>17be6eae40795ec068ce77a05fcb1c47f7ac42dfba160261719d4087</host_uuid>
    <host_name>my-ucs-3</host_name>
    <vm_uuid>cb86a952-c030-46f6-96f6-e81069bcea3a</vm_uuid>
    <interfaces>
      <interface>
        <network_uuid>943fd94e-79f8-400c-b442-3506f102721a</network_uuid>
        <gateway>192.168.0.1</gateway>
        <ip_address>192.168.0.135</ip_address>
        <mac_address>fa:16:3e:3c:17:b0</mac_address>
        <netmask>255.255.255.0</netmask>
        <níc_id>0</níc_id>
        <port_forwarding></port_forwarding>
        <port_uuid>263eaf20-2662-4a6b-a1f1-ed76001a1b5c</port_uuid>
        <security_groups></security_groups>
        <subnet_uuid>e313b95c-ca1f-4c81-8d60-c9e721a85d0b</subnet_uuid>
        <type>virtual</type>
      </interface>
    </interfaces>
    <vm_group_name>overidegrp2</vm_group_name>
    <vm_name>test-dep1-cirros_overid_0_cfeefcee-a1fe-4e94-9ffc-81792b265788</vm_name>
    <vm_state_machine_state>VM_SHUTOFF_STATE</vm_state_machine_state>
  </deployment_details>
  <deployment_name>test-dep1-cirros</deployment_name>
  <deployment_stage>VM_STOPPED</deployment_stage>
  <external_deployment_id>5c278010-ad0f-4e29-bdce-f4b6c6946c38</external_deployment_id>
  <external_tenant_id>29f2cd7934dc4311ad3a34d72d1ab7b8</external_tenant_id>
  <internal_deployment_id>test-tenant1test-dep1-cirros</internal_deployment_id>
```

```
<internal_tenant_id>test-tenant1</internal_tenant_id>
<service_state_machine_state>SERVICE_STOPPED_STATE</service_state_machine_state>
</deployment>
```

After the stop deployment operation is done successfully, ESC will send a SERVICE_STOPPED callback to the client with the result. Example callback:

```
HTTP/1.1 200 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: 5e47b5ff-bc59-4ece-b15b-8941910def74
ESC-Status-Code: 200
ESC-Status-Message: Service group suspension completed successfully

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<deployment xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <datacenter>
    <default>false</default>
  </datacenter>
  <deployment_details>
    <host_uuid>17be6eae40795ec068ce77a05fcb1c47f7ac42dfba160261719d4087</host_uuid>
    <host_name>my-ucs-3</host_name>
    <vm_uuid>cb86a952-c030-46f6-96f6-e81069bcea3a</vm_uuid>
    <interfaces>
      <interface>
        <network_uuid>943fda9e-79f8-400c-b442-3506f102721a</network_uuid>
        <gateway>192.168.0.1</gateway>
        <ip_address>192.168.0.135</ip_address>
        <mac_address>fa:16:3e:3c:17:b0</mac_address>
        <netmask>255.255.255.0</netmask>
        <nic_id>0</nic_id>
        <port_forwarding></port_forwarding>
        <port_uuid>263eaf20-2662-4a6b-a1f1-ed76001a1b5c</port_uuid>
        <security_groups></security_groups>
        <subnet_uuid>e313b95c-ca1f-4c81-8d60-c9e721a85d0b</subnet_uuid>
        <type>virtual</type>
      </interface>
    </interfaces>
    <vm_group_name>overridegrp2</vm_group_name>
    <vm_name>test-dep1-cirros_overid_0_cfeefcee-a1fe-4e94-9ffc-81792b265788</vm_name>
    <vm_state_machine_state>VM_SHUTOFF_STATE</vm_state_machine_state>
  </deployment_details>
  <deployment_name>test-dep1-cirros</deployment_name>
  <deployment_stage>SERVICE_STOPPED</deployment_stage>
  <external_deployment_id>5c278010-ad0f-4e29-bdce-f4b6c6946c38</external_deployment_id>
  <external_tenant_id>29f2cd7934dc4311ad3a34d72d1ab7b8</external_tenant_id>
  <internal_deployment_id>test-tenant1test-dep1-cirros</internal_deployment_id>
  <internal_tenant_id>test-tenant1</internal_tenant_id>
  <service_state_machine_state>SERVICE_STOPPED_STATE</service_state_machine_state>
</deployment>
```

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
Callback-ESC-Events	(required)	Callback URL for ESC event notifications	header	string
internal_tenant_id	(required)	Internal tenant ID (max length 72 characters)	path	string
internal_deployment_id	(required)	Internal deployment ID (max length 72 characters)	path	string
body	(required)	Deployment operation payload specifying the type of operation	body	<div style="display: flex; justify-content: space-between;"> Model Model Schema </div> <pre>{ "operation": "stop", "properties": {} }</pre>
Parameter content type:		application/xml ▾	Click to set as parameter value	

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Deployment operation request accepted		
400	Missing callback or, Deployment operation is not applicable		
404	Deployment or tenant not found		

Try it out!

08-VM Operations : Operations to a VM

POST /v0/{internal_tenant_id}/deployments/recovery-vm/{vm_name}

Handle recovery VM operation request with the operation type as payload

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	<input type="text"/>	Callback URL for notifications	header	string
Callback-ESC-Events	<input type="text"/>	Callback URL for ESC event notifications	header	string
internal_tenant_id	(required)	Internal tenant ID (max length 72 characters)	path	string
vm_name	(required)	VM name	path	string
body	(required)	Recovery VM operation payload specifying the type of operation: recovery_do	body	<div style="display: flex; justify-content: space-between;"> Model Model Schema </div> <pre>{ "operation": "string", "checkVmBeforeRecovery": true, "properties": {} }</pre>
		Parameter content type:	application/xml ▾	

Click to set as parameter value

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Recovery VM operation request accepted		
400	Recovery VM operation is not applicable		
404	VM or tenant not found		

[Try it out!](#)

POST /v0/{internal_tenant_id}/deployments/snapshot-vm/{vm_name}

Handle VM snapshot operation request with the operation type as payload

Implementation Notes

vm_operation_notes

Parameters

Parameter	Value	Description	Parameter Type	Data Type
-----------	-------	-------------	----------------	-----------

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for notifications	header	string
Callback-ESC-Events	(required)	Callback URL for ESC event notifications	header	string
internal_tenant_id	(required)	Internal tenant ID (max length 72 characters)	path	string
vm_name	(required)	VM name	path	string
body	(required)	VM operation payload specifying the type of operation	body	<div style="display: flex; justify-content: space-between;"> Model Model Schema </div> <pre>{ "bootableVolumeSnapshotId": "string", "operation": "snapshot", "name": "string", "id": "string", "metadata": {} }</pre> <p>Click to set as parameter value</p>

Response Messages

HTTP Status Code	Reason	Response Model	Headers
201	VM snapshot operation request accepted		
400	Missing callback or, VM operation is not applicable		
404	VM or tenant not found		

Try it out!

POST /v0/{internal_tenant_id}/deployments/vm/{vm_name}

Handle VM operation request with the operation type as payload

Implementation Notes

Performs actions like stop, start, reboot, disable_monitoring or enable_monitoring on an existing VM managed by ESC. Example request:

```
POST /v0/tenants/test-tenant1/deployments/vm/test-dep1-cirros_overid_0_cfeefcee-a1fe-4e94-9ffc-81792b265788
Content-Type: application/xml
Accept: application/json
Callback: http://127.0.0.1:9010/
Callback-ESC-Events: http://127.0.0.1:9010/

Body:
<vm_operation xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
    <operation>stop</operation>
</vm_operation>
```

After the VM stop operation is done, ESC will send a VM_STOP_COMPLETE callback to the client with the result. Example callback:

```
HTTP/1.1 200 OK
Content-Type: application/xml; charset=UTF-8
ESC_TRANSACTION_ID: 4546c40a-d6e3-4abe-a7e7-51af4fc5362
ESC-Status-Code: 200
ESC-Status-Message: Successfully stopped VM [test-dep1-cirros_overid_0_cfeefcee-a1fe-4e94-9ffc-81792b265788]

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<esc_event xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
    <deployment_name>test-dep1-cirros</deployment_name>
    <event_details></event_details>
    <event_type>VM_STOP_COMPLETE</event_type>
    <external_deployment_id>5c278010-ad0f-4e29-bdce-f4b6c6946c38</external_deployment_id>
    <external_tenant_id>29f2cd7934dc4311ad3a34d72d1ab7b8</external_tenant_id>
    <internal_deployment_id>test-tenant1test-dep1-cirros</internal_deployment_id>
    <internal_tenant_id>test-tenant1</internal_tenant_id>
    <vm_source>
        <interfaces>
            <network_uuid>943fd9a9e-79f8-400c-b442-3506f102721a</network_uuid>
            <gateway>192.168.0.1</gateway>
            <ip_address>192.168.0.135</ip_address>
            <mac_address>fa:16:3e:3c:17:b0</mac_address>
            <netmask>255.255.255.0</netmask>
            <nic_id>0</nic_id>
            <port_forwarding></port_forwarding>
            <port_uuid>263eaf20-2662-4a6b-a1f1-ed76001a1b5c</port_uuid>
            <security_groups></security_groups>
            <subnet_uuid>e313b95c-ca1f-4c81-8d60-c9e721a85d0b</subnet_uuid>
            <type>virtual</type>
        </interfaces>
        <host_uuid>17be6eae40795ec068ce77a05fc1c47f7ac42dfba160261719d4087</host_uuid>
        <host_name>my-ucs-3</host_name>
        <vm_uuid>cb86a952-c030-46f6-96f6-e81069bcea3a</vm_uuid>
    </vm_source>
</esc_event>
```

```

<vm_group_name>overridegrp2</vm_group_name>
<vm_name>test-dep1-cirros_overid_0_cfeefcee-a1fe-4e94-9ffc-81792b265788</vm_name>
</vm_source>
</esc_event>

```

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for notifications	header	string
Callback-ESC-Events	(required)	Callback URL for ESC event notifications	header	string
internal_tenant_id	(required)	Internal tenant ID (max length 72 characters)	path	string
vm_name	(required)	VM name	path	string
body	(required)	VM operation payload specifying the type of operation	body	Model Model Schema <div style="background-color: #ffffcc; padding: 5px;"> <pre>{ "operation": "stop" }</pre> </div>
Parameter content type:		Click to set as parameter value		
<input type="button" value="application/xml ▾"/>				

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	VM operation request accepted		
400	Missing callback or, VM operation is not applicable		
404	VM or tenant not found		
Try it out!			

09-Configuration Parameters

GET	/v0/config/{category}/{key}	Retrieve a ESC config parameters under a category, with a given key
-----	-----------------------------	---

Implementation Notes

Retrieve a ESC config parameters under a category, with a given key

Parameters

Parameter	Value	Description	Parameter Type	Data Type
category	(required)	ESC config parameter category	path	string
key	(required)	ESC config parameter key	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Get key under category request accepted.		
400	Invalid key or category name provided.		
404	Key or category not found.		

Try it out!

POST /v0/config/{category}/{key}

Create a new key under a category.

Implementation Notes

Create a new key under a catgeory.

Response Class (Status 200)

Model | Model Schema

```
{
  "category": "DEFAULT",
  "key": "MAX_LOGS",
  "value": {},
  "type": "STRING"
}
```

Response Content Type application/xml ▾

Parameters

Parameter	Value	Description	Parameter Type	Data Type

Parameter	Value	Description	Parameter Type	Data Type
category	(required)	ESC config parameter category	path	string
key	(required)	ESC config parameter key	path	string
body	(required)	ESC config parameter value	body	string
Parameter content type:				application/json ▾
Try it out!				

PUT /v0/config/{category}/{key}/{value} Change an ESC config parameter under a category, with a given key

Implementation Notes

Change an ESC config parameter under a category, with a given key.

Format: PUT /v0/config/{category}/{key}/{value}

Example request:

curl -X PUT -H "accept: Application/xml" <http://127.0.0.1:8080/ESCManger/v0/config/log/level/debug>

Example response:

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<escconfigparameter>
  <category>LOG</category>
  <key>LEVEL</key>
  <type>STRING</type>
  <value xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xs="http://www.w3.org/2001/XMLSchema">INFO</value>
</escconfigparameter>
```

Details of Config Parameters: Please refer to installation and user guide for more details.

Category: DEFAULT Key: VM_RECOVERY_RETRIES_MAX Default Value: 3 Type: Int Description: Number of maximum recovery attempts allowed per VM.

Category: OPENSTACK Key: ENDPOINT Default Value: adminURL Type: String Description: The parameter to set up the keystone endpoint value of ESC. Options : adminURL, publicURL

Category: LOG Key: LEVEL Default Value: INFO Type: String Description: Level of logging of ESCManager. Options: INFO, TRACE, DEBUG.

Category: AFFINITY Key: FILTER Default Value: SameHostFilter Type: String Description: A constant string used to build PolicyEngine and initializing VM policy table. Options: SameHostFilter, ServerGroupAffinity

Category: ANTI-AFFINITY Key: FILTER Default Value: DifferentHostFilter Type: String Description: A constant string used to build PolicyEngine and initializing VM policy table. Options: DifferentHostFilter, ServerGroupAffinity

Parameters

Parameter	Value	Description	Parameter Type	Data Type
category	(required)	ESC config parameter category	path	string
key	(required)	ESC config parameter key	path	string
value	(required)	ESC config parameter value	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Update value request accepted.		
400	Invalid request.		
404	Associated resource not found.		
406	Not acceptable.		
409	Conflicting resource.		
500	Internal server error.		

Try it out!

GET	/v0/config	Retrieve all ESC config parameters
-----	------------	------------------------------------

Implementation Notes

Retrieve all ESC config parameters

Response Messages

HTTP Status Code	Reason	Response Model	Headers
------------------	--------	----------------	---------

HTTP Status Code	Reason	Response Model	Headers
200	Get all parameters request accepted		

[Try it out!](#)

GET	/v0/config/{category}	Retrieve all ESC config parameters under a category
-----	-----------------------	---

Implementation Notes

Retrieve all ESC config parameters under a category

Parameters

Parameter	Value	Description	Parameter Type	Data Type
category	(required)	ESC config parameter category	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Get category request accepted.		
400	Invalid category name provided.		
404	Category not found.		

[Try it out!](#)

10-Volumes : Manage ESC volumes

DELETE	/v0/{internalTenantId}/volumes/{internalVolumeId}	Delete a volume from an existing tenant in ESC
--------	---	--

Implementation Notes

Delete a volume from ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string

Parameter	Value	Description	Parameter Type	Data Type
internalVolumeId	(required)	Internal volume ID (max length 72 characters)	path	string
internalTenantId	(required)	Internal tenant ID of the volume (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid request		
500	Internal server error		

[Try it out!](#)

GET /v0/{internalTenantId}/volumes/{internalVolumeId} Get a volume by its tenant and internal volume ID

Implementation Notes

Only volumes created using ESC will be checked

Parameters

Parameter	Value	Description	Parameter Type	Data Type
internalTenantId	(required)	Internal tenant ID of the volume (max length 72 characters)	path	string
internalVolumeId	(required)	Internal volume ID (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
404	Volume Id not found		

[Try it out!](#)

POST

/v0/{internalTenantId}/volumes/{internalVolumeId}

Create a volume under an existing tenant in ESC

Implementation Notes

Create a volume in ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalTenantId	(required)	Internal tenant ID of the volume (max length 72 characters)	path	string
internalVolumeId	(required)	Internal volume ID (max length 72 characters)	path	string
body	(required)	Volume configuration payload	body	<div style="display: flex; justify-content: space-between;"> Model Model Schema </div> <pre>{ "external_volume_id": "string", "size": "string", "sizeunit": "string", "bus": "string", "type": "string", "outOfBand": true, "bootIndex": "string", "name": "string", "format": "string", "storageLocation": "string", "external_tenant_id": "string", "internal_tenant_id": "string", "internal_volume_id": "string", "volid": 0, "event_type": "CREATE_VOLUME", "image": "string" }</pre>
Parameter content type:		<div style="border: 1px solid #ccc; padding: 2px; display: inline-block;"> application/xml ▾ </div>		
Click to set as parameter value				

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid request		

HTTP Status Code	Reason	Response Model	Headers
404	Volume Id not found		
409	Conflicting request		
503	Unable to query VIM		

[Try it out!](#)

GET	/v0/{internalTenantId}/volumes	Get all volumes under a tenant
-----	--------------------------------	--------------------------------

Implementation Notes

All volumes under that tenant in ESC will be returned as a List

Parameters

Parameter	Value	Description	Parameter Type	Data Type
internalTenantId	(required)	Internal tenant ID of the volume (max length 72 characters)	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		

[Try it out!](#)

11-ESC Operation Mode

GET	/v0/operationmode	Get operation mode in ESC
-----	-------------------	---------------------------

Implementation Notes

Set operation mode in ESC

Response Class (Status 200)

Model | Model Schema

```
{
  "message": "string",
  "mode": "string"
}
```

Response Content Type application/xml ▾

Try it out!

POST /v0/operationmode/{escOpMode}

Set operation mode in ESC

Implementation Notes

Set operation mode in ESC

Response Class (Status 200)

Model Model Schema

```
{  
  "message": "string",  
  "mode": "string"  
}
```

Response Content Type application/xml ▾

Parameters

Parameter	Value	Description	Parameter Type	Data Type
escOpMode	MAINTENANCE ▾	ESC maintenance mode.	path	string

Try it out!

12-Host Actions

POST /v0/hosts/{hostName}/enable

Enable a host

Implementation Notes

To enable a host

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback- ESC-Events	(required)	Callback URL for host action notifications	header	string
hostName	(required)	Target host name	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
default	successful operation		
Try it out!			

POST	/v0/hosts/{hostName}/disable	Disable a host		
Implementation Notes				
To disable a host				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
Callback- ESC-Events	(required)	Callback URL for host action notifications	header	string
hostName	(required)	Target host name	path	string
Response Messages				
HTTP Status Code	Reason	Response Model	Headers	
default	successful operation			
Try it out!				

GET	/v0/hosts/{hostName}/status	Get the current status of the host		
Implementation Notes				
This is to see if the host can be scheduled to deploy instances				
Response Class (Status 200)				
Response Content Type <input type="button" value="application/xml ▾"/>				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
Client- Transaction- Id			header	string
hostName	(required)		path	string
Try it out!				

13-ESC VIM Connectors : Manage ESC VIM Connectors

GET	/v0/vims/default_vim_connector	Get default VIM Connector name
-----	--------------------------------	--------------------------------

Response Class (Status 200)

Model | Model Schema

```
{  
  "defaultVimConnectorId": "string",  
  "event_type": "string"  
}
```

Response Content Type application/xml ▾

Try it out!

POST	/v0/vims/default_vim_connector
	Create a Default VIM connector in ESC

Implementation Notes

Create a Default VIM connector in ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
body	(required)	Default VIM Connector configuration payload	body	<p>Model Model Schema</p> <pre>{ "defaultVimConnectorId": "string", "event_type": "string" }</pre>

Parameter content type:

application/xml ▾

Click to set as parameter value

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
500	Internal Server Error		

Try it out!

GET

/v0/vims

Get all VIM Connectors

Implementation Notes

All VIM Connectors in ESC will be returned as a List

Response Class (Status 200)

Model Model Schema

```
[  
  {  
    "id": "string",  
    "type": "OPENSTACK",  
    "properties": {  
      "property": [  
        {  
          "name": "string",  
          "value": "string",  
          "encrypted_value": "string"  
        }  
      ]  
    },  
    "event_type": "string"  
  }  
]
```

Response Content Type

Try it out!

POST

/v0/vims

Create a VIM connector in ESC

Implementation Notes

Create a VIM connector in ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	VIM Connector configuration payload	body	<div style="display: flex; justify-content: space-between;"> Model Model Schema </div> <pre>{ "id": "string", "type": "OPENSTACK", "properties": { "property": [{ "name": "string", "value": "string", "encrypted_value": "string" }] }, "event_type": "string" }</pre> <p>Click to set as parameter value</p>

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
500	Internal Server Error		

[Try it out!](#)

DELETE	/v0/vims/{vim_id}	Delete a VIM Connector from ESC		
Implementation Notes				
Delete a VIM Connector from ESC				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
vim_id	(required)	VIM ID	path	string
Response Messages				
HTTP Status Code	Reason	Response Model	Headers	

HTTP Status Code	Reason	Response Model	Headers
200	VIM Connector deletion request accepted		
400	Invalid Request		
404	VIM Id not found		
500	Internal Server Error		
Try it out!			

GET	/v0/vims/{vim_id}	Get a VIM Connector by its id		
Parameters				
Parameter Value Description Parameter Type Data Type				
vim_id <input type="text" value=""/>		VIM ID	path	string
Response Messages				
HTTP Status Code	Reason	Response Model	Headers	
200	Get request accepted			
404	VIM Id not found			
Try it out!				

PUT	/v0/vims/{vim_id}	Update an existing VIM connector in ESC
Implementation Notes		
Update an existing VIM connector in ESC		
Parameters		
Parameter	Value	Description Parameter Type Data Type
Callback	<input type="text" value=""/>	Callback URL for ESC notifications header string
vim_id	<input type="text" value=""/>	VIM ID path string

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	Update VIM Connector configuration payload	body	Model Model Schema <pre>{ "id": "string", "type": "OPENSTACK", "properties": { "property": [{ "name": "string", "value": "string", "encrypted_value": "string" }] }, "event_type": "string" }</pre>

Parameter content type: application/xml ▾

Click to set as parameter value

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
500	Internal Server Error		

Try it out!

PUT	/v0/vims/{vim_id}/check_status	Trigger VIM connector status checking		
Implementation Notes				
Trigger VIM connector status checking				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
vim_id	(required)	VIM ID	path	string
Response Messages				
HTTP Status Code	Reason	Response Model	Headers	
200	Request accepted			
400	Invalid Request			

HTTP Status Code	Reason	Response Model	Headers
404	Not Found		
500	Internal Server Error		
Try it out!			

14-ESC VIM Users : Manage ESC VIM Users

GET	/v0/vims/{vim_id}/vim_users	Get all VIM Users
-----	-----------------------------	-------------------

Implementation Notes

All VIM Users in ESC will be returned as a List

Parameters

Parameter	Value	Description	Parameter Type	Data Type
vim_id	(required)		path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Get request accepted		
404	Unknown VIM Id provided		
Try it out!			

POST	/v0/vims/{vim_id}/vim_users	Create a VIM user under an existing VIM in ESC
------	-----------------------------	--

Implementation Notes

Create a VIM user in ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
vim_id	(required)	Vim id	path	string

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	Vim user configuration payload	body	<div style="display: flex; align-items: center;"> Model Model Schema </div> <pre>{ "credentials": { "properties": { "property": [{ "name": "string", "value": "string", "encrypted_value": "string" }] } }, "id": "string", "vim_id": "string", "event_type": "string" }</pre> <p>Click to set as parameter value</p>

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
500	Internal Server Error		

[Try it out!](#)

DELETE	/v0/vims/{vim_id}/vim_users/{vim_user_id}	Delete a VIM User from ESC		
Implementation Notes				
Delete a VIM User from ESC				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
vim_id	(required)	Vim id	path	string
vim_user_id	(required)	Vim user id	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
404	VIM User Id not found		
500	Internal Server Error		

Try it out!

GET

/v0/vims/{vim_id}/vim_users/{vim_user_id}

Get a VIM User by its id

Parameters

Parameter	Value	Description	Parameter Type	Data Type
vim_id	(required)	Vim id	path	string
vim_user_id	(required)	Vim user id	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Get request accepted		
404	VIM User Id not found		

Try it out!

PUT

/v0/vims/{vim_id}/vim_users/{vim_user_id}

Update a VIM user under an existing VIM in ESC

Implementation Notes

Update a VIM user in ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
vim_id	(required)	Vim id	path	string

Parameter	Value	Description	Parameter Type	Data Type
vim_user_id	(required)	Vim user id	path	string
body	(required)	Vim user configuration payload	body	<div style="display: flex; justify-content: space-between;"> Model Model Schema </div> <pre>{ "credentials": [{ "properties": [{ "property": [{ "name": "string", "value": "string", "encrypted_value": "string" }] }], "id": "string", "vim_id": "string", "event_type": "string" }] }</pre> <p>Click to set as parameter value</p>
Parameter content type:		application/xml		

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
400	Invalid Request		
500	Internal Server Error		

Try it out!

15-System States

POST	/v0/systemstate/{name}/reset	Reset system state of a given name		
Implementation Notes				
Reset system state of a given name				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
name	(required)	System state name	path	string
Response Messages				

HTTP Status Code	Reason	Response Model	Headers
200	Reset system state of specified name request accepted.		
404	Name not found.		
Try it out!			

GET	/v0/systemstate/{name}	Retrieve system state of a given name		
Implementation Notes				
Retrieve system state of a given name				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
name	(required)	System state name	path	string
Response Messages				
HTTP Status Code	Reason	Response Model	Headers	
200	Get system state of specified name request accepted.			
404	Name not found.			
Try it out!				

16-File Servers

DELETE	/v0/fileserver/{internalServerId}	Delete a File Server		
Implementation Notes				
Delete a File Server				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalServerId	(required)	File Server ID	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
404	Not found		
500	Internal server error		

Try it out!

GET

/v0/fileserver/{internalServerId}

Get specific File Server

Implementation Notes

Matching File server will be returned if exists

Parameters

Parameter	Value	Description	Parameter Type	Data Type
internalServerId	(required)	File Server Id	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
404	Not found		

Try it out!

POST

/v0/fileserver/{internalServerId}

Create a File Server

Implementation Notes

Create a File Server

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalServerId	(required)	File Server ID	path	string

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	ESC datamodel with the file server payload	body	string
Parameter content type:				
application/xml ▾				

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
204	No content		
400	Invalid Request		
409	Conflicting Request		

Try it out!

PUT	/v0/fileserver/{internalServerId}	Update a File Server		
Implementation Notes				
Update a File Server				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalServerId	(required)	File Server ID	path	string
body	(required)	ESC datamodel with the file server payload	body	string
Parameter content type:				
application/xml ▾				
Response Messages			Headers	
HTTP Status Code	Reason	Response Model	Headers	

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
204	No content		
400	Invalid Request		
404	Not Found		

[Try it out!](#)

GET	/v0/fileserver	Get all File Servers								
Implementation Notes										
All file servers created will be returned as a List										
Response Messages										
<table border="1"> <thead> <tr> <th>HTTP Status Code</th><th>Reason</th><th>Response Model</th><th>Headers</th></tr> </thead> <tbody> <tr> <td>200</td><td>Request accepted</td><td></td><td></td></tr> </tbody> </table>			HTTP Status Code	Reason	Response Model	Headers	200	Request accepted		
HTTP Status Code	Reason	Response Model	Headers							
200	Request accepted									
Try it out!										

17-Dynamic Mappings

DELETE	/v0/dynamic_mapping/metrics	Delete all non-CORE dynamic mapping metrics from ESC								
Implementation Notes										
Deletes all non-CORE dynamic mapping metrics from ESC										
Response Messages										
<table border="1"> <thead> <tr> <th>HTTP Status Code</th><th>Reason</th><th>Response Model</th><th>Headers</th></tr> </thead> <tbody> <tr> <td>200</td><td>Delete all non-core metrics request accepted</td><td></td><td></td></tr> </tbody> </table>			HTTP Status Code	Reason	Response Model	Headers	200	Delete all non-core metrics request accepted		
HTTP Status Code	Reason	Response Model	Headers							
200	Delete all non-core metrics request accepted									
Try it out!										

GET	/v0/dynamic_mapping/metrics	Retrieve all the dynamic mapping metrics defined in ESC
Implementation Notes		
Retrieves all the dynamic mapping metrics defined in ESC		

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Get all metrics request accepted		

Try it out!

POST /v0/dynamic_mapping/metrics

Create new dynamic mapping metric(s)

Implementation Notes

create_dynamic_mapping_metrics_notes

Parameters

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	Metrics payload	body	string

Parameter content type:

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Create new metric request accepted		
400	'Exception Message' or 'No metric definition found.'		
409	Metric [metricName] already exists.		

Try it out!

DELETE /v0/dynamic_mapping/metrics/{metric_name}

Delete a dynamic mapping metric from ESC

Implementation Notes

Deletes a dynamic mapping metric from ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
<code>metric_name</code>	(required)	Name of the metric you want to delete	path	string
HTTP Status Code	Reason	Response Model	Headers	
200	Delete metric request accepted			
400	'Invalid metric name provided', 'Metric [metricName] is a CORE metric, cannot delete.', or 'Metric [metricName] is currently referenced in a deployment, cannot delete.'			
404	Metric [metricName] not found.			
Try it out!				

GET	/v0/dynamic_mapping/metrics/{metric_name}	Retrieve a dynamic mapping metric by name										
Implementation Notes <p>Retrieves a dynamic mapping metric by name</p>												
Parameters												
<table border="1"> <thead> <tr> <th>Parameter</th><th>Value</th><th>Description</th><th>Parameter Type</th><th>Data Type</th></tr> </thead> <tbody> <tr> <td><code>metric_name</code></td><td>(required)</td><td>Name of the metric you want to retrieve</td><td>path</td><td>string</td></tr> </tbody> </table>			Parameter	Value	Description	Parameter Type	Data Type	<code>metric_name</code>	(required)	Name of the metric you want to retrieve	path	string
Parameter	Value	Description	Parameter Type	Data Type								
<code>metric_name</code>	(required)	Name of the metric you want to retrieve	path	string								
HTTP Status Code	Reason	Response Model	Headers									
200	Get metric request accepted											
400	Invalid metric name provided [metricName].											
404	Metric [metricName] not found.											
Try it out!												

DELETE	/v0/dynamic_mapping/actions/{action_name}	Delete a dynamic mapping action from ESC
--------	---	--

Implementation Notes

Deletes a dynamic mapping action from ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
<code>action_name</code>	(required)	Name of the action you want to delete	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Delete action request accepted		
400	'Invalid action name provided', 'Action [actionName] is a CORE action, cannot delete.', or 'Action [actionName] is currently referenced in a deployment, cannot delete.'		
404	Action [actionName] not found.		

Try it out!

GET

/v0/dynamic_mapping/actions/{action_name}

Retrieve a dynamic mapping action by name

Implementation Notes

Retrieves a dynamic mapping action by name

Parameters

Parameter	Value	Description	Parameter Type	Data Type
<code>action_name</code>	(required)	Name of the action you want to retrieve	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Get action request accepted		
400	Invalid action name provided [actionName].		
404	Action [actionName] not found.		

Try it out!

DELETE /v0/dynamic_mapping/actions

Delete all non-CORE dynamic mapping actions from ESC

Implementation Notes

Deletes all non-CORE dynamic mapping actions from ESC

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Delete all non-core actions request accepted		

Try it out!

GET /v0/dynamic_mapping/actions

Retrieve all the dynamic mapping actions defined in ESC

Implementation Notes

Retrieves all the dynamic mapping actions defined in ESC

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Get all actions request accepted		

Try it out!

POST /v0/dynamic_mapping/actions

Create new dynamic mapping action(s)

Implementation Notes

create_dynamic_mapping_actions_notes

Parameters

Parameter	Value	Description	Parameter Type	Data Type

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	Actions payload	body	string
Parameter content type:				
<input type="button" value="application/xml ▾"/>				

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Create new action request accepted		
400	'Exception Message' or 'No action definition found.'		
409	Action [actionName] already exists.		

18-VM Snapshots

GET	/v0/snapshots	Get all VMSnapshots		
Implementation Notes				
Return all VMSnapshots created as a List				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
internalTenantId	<input type="text"/>		query	string
generatedVMName	<input type="text"/>		query	string
Response Messages				
HTTP Status Code	Reason	Response Model	Headers	
200	Request accepted			

POST	/v0/snapshots/{snapshotId}/volumes	Create a volume from a snapshot
------	------------------------------------	---------------------------------

Implementation Notes

Creation of a bootable volume from an ESC created volume snapshot. This is an asynchronous operation

Parameters

Parameter	Value	Description	Parameter Type	Data Type
snapshotId	(required)	Snapshot ID	path	string
Callback	(required)	Callback URL for ESC notifications	header	string
body	(required)	Volume name	body	Model Model Schema {} Click to set as parameter value

Parameter content type:

application/json ▾

Response Messages

HTTP Status Code	Reason	Response Model	Headers
202	Request Accepted		
404	Snapshot not found		

Try it out!

DELETE /v0/snapshots/{snapshotIdOrName} Handle VM snapshot delete request

Implementation Notes

Delete VM snapshot

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for notifications	header	string
Callback-ESC-Events	(required)	Callback URL for ESC event notifications	header	string
snapshotIdOrName	(required)	Snapshot Id/Name	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	VM snapshot delete operation request accepted		
404	Snapot image not found		
409	The request could not be processed because snapshot name is not unique		

[Try it out!](#)

19-Routers : Manage ESC Routers

DELETE	/v0/{internalTenantId}/routers/{internalRouterId}	Delete a router from an existing tenant in ESC		
Implementation Notes				
Delete a router from ESC				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalRouterId	(required)	Internal router ID (max length 72 characters)	path	string
internalTenantId	(required)	Internal tenant ID of the router (max length 72 characters)	path	string
Response Messages				
HTTP Status Code	Reason	Response Model	Headers	
200	Request accepted			
400	Invalid request			
500	Internal server error			

[Try it out!](#)

POST	/v0/{internalTenantId}/routers/{internalRouterId}	Create a router under an existing tenant in ESC
-------------	---	---

Implementation Notes

Create a router in ESC

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalTenantId	(required)	Internal tenant ID of the network (max length 72 characters)	path	string
internalRouterId	(required)	Internal router ID (max length 72 characters)	path	string

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	Router configuration payload	body	<div style="display: flex; justify-content: space-between;"> Model Model Schema </div> <div style="background-color: #ffffcc; padding: 10px; border: 1px solid #ccc; margin-top: 10px;"> <pre>{ "internal_tenant_id": "string", "internal_router_id": "string", "name": "string", "external_tenant_id": "string", "tenant_name": "string", "external_router_id": "string", "admin_state": true, "external_network": "string", "description": "string", "external_network_id": "string", "interface": [{ "internalAttachInterfaceId": "string", "routerName": "string", "subnetId": "string", "internal_router_id": "string", "router_id": "string", "subnet": "string", "port_id": "string", "event_type": "ATTACH_INTERFACE" }], "route": [{ "routerId": "string", "internalId": "string", "internal_router_id": "string", "destination": "string", "next_hop": "string", "route_name": "string", "event_type": "ATTACH_INTERFACE" }], "event_type": "CREATE_ROUTER", "snat_enable": true, "isdistributed": true }</pre> </div>
Parameter content type: application/xml ▾				
Click to set as parameter value				
<h2>Response Messages</h2>				
HTTP Status Code	Reason	Response Model	Headers	
200	Request accepted			
400	Invalid request			
404	Router Id not found			

HTTP Status Code	Reason	Response Model	Headers
409	Conflicting request		
503	Unable to query VIM		
Try it out!			

PUT	/v0/{internalTenantId}/routers/{internalRouterId}	Update a Router		
Implementation Notes				
Update a Router				
Parameters				
Parameter	Value	Description	Parameter Type	Data Type
Callback	(required)	Callback URL for ESC notifications	header	string
internalTenantId	(required)	Internal tenant ID of the network (max length 72 characters)	path	string
internalRouterId	(required)	Internal router ID (max length 72 characters)	path	string

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	Router configuration payload	body	<div style="display: flex; justify-content: space-between;"> Model Model Schema </div> <pre>{ "internal_tenant_id": "string", "internal_router_id": "string", "name": "string", "external_tenant_id": "string", "tenant_name": "string", "external_router_id": "string", "admin_state": true, "external_network": "string", "description": "string", "external_network_id": "string", "interface": [{ "internalAttachInterfaceId": "string", "routerName": "string", "subnetId": "string", "internal_router_id": "string", "router_id": "string", "subnet": "string", "port_id": "string", "event_type": "ATTACH_INTERFACE" }], "route": [{ "routerId": "string", "internalId": "string", "internal_router_id": "string", "destination": "string", "next_hop": "string", "route_name": "string", "event_type": "ATTACH_INTERFACE" }], "event_type": "CREATE_ROUTER", "snat_enable": true, "isdistributed": true }</pre> <p>Click to set as parameter value</p>

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	Request accepted		
204	No content		
400	Invalid Request		

HTTP Status Code	Reason	Response Model	Headers
404	Not Found		
Try it out!			

SSL Management

PUT	/internal/ssl/reload	Reload ESC Truststore from file system												
<h3>Implementation Notes</h3> <p>Reload ESC Truststore from file system</p>														
<h3>Response Messages</h3>														
<table><thead><tr><th>HTTP Status Code</th><th>Reason</th><th>Response Model</th><th>Headers</th></tr></thead><tbody><tr><td>204</td><td>ESC Truststore reloaded successfully</td><td></td><td></td></tr><tr><td>500</td><td>Failed to reload ESC truststore</td><td></td><td></td></tr></tbody></table>			HTTP Status Code	Reason	Response Model	Headers	204	ESC Truststore reloaded successfully			500	Failed to reload ESC truststore		
HTTP Status Code	Reason	Response Model	Headers											
204	ESC Truststore reloaded successfully													
500	Failed to reload ESC truststore													
Try it out!														

[BASE URL: /ESCManger , API VERSION: 2.2.0]